



---

## Classic XXL 40

---

### Applications

Castrol Classic XXL 40 is high quality monograde engine oil recommended for single and multi-cylinder engines under road and competition conditions.

Castrol Classic XXL 40 contains selected additives to control high temperature 'varnish', give good anti-wear performance and prevent the build up of low temperature 'sludge'.

Castrol XXL 40 must not be mixed with either Castrol R 30 or R 40 or any other synthetic or castor/synthetic based oils.

---

### Features / Benefits

#### Cars

Summer use in all types of petrol engines

Winter use in engines which would otherwise have a high oil consumption

Some manually operated gearboxes

#### Motor Cycles

Summer use in most twin-cylinder 4-stroke engines

Certain motorcycle gearboxes

---

### Specifications / Performance

API SB

---

### Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

---

### Health, Safety and Environment

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products.

Castrol (UK) Ltd. or its subsidiaries will not accept liability if the product is used other than in the manner or with the precautions or for the purpose/s specified. Before the product is used other than as directed, advice should be obtained from the local Castrol office.

---

### Typical Characteristics

---

Test Methods

Units

Value:

---

<i>Test</i>	<i>Method(s)</i>	<i>Unit</i>	<i>Typical</i>
Density @ 15C, Relative	ASTM D4052		0.885
Appearance	Visual		clear and bright
Viscosity, Kinematic 100C	IP 71	mm <sup>2</sup> /s	14.89
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	155
Calcium, % wt	ASTM D4951	% wt	0.005
Phosphorus, % wt	ASTM D4951	% wt	0.0185
Zinc, % wt	ASTM D4951	% wt	
Viscosity Index	ASTM D2270	None	95
Flash Point, PMCC	ASTM D93	°C	200

---

*The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.*

**This Data sheet and information it contains is considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication. It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. No statement made in this publication shall be construed as a permission, recommendation or authorisation given or implied to practice any patented invention without a valid licence.**

**The Seller shall not be responsible for any loss or damage resulting from any hazards or risks identified in the data sheet and which are associated with petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned).**

Castrol UK Ltd, Wakefield House, Pipers Way, SWINDON, Wiltshire. SN3 1RE [www.castrol.com/uk](http://www.castrol.com/uk)  
 Telephone: 01793 512712  
 Automotive Technical Helpline: 01793 452222  
 Orders/Enquiries: 0845 6008125 (Workshop Customer Order Line) 0845 6008131 (Retail Customer Order Line)

Castrol Ireland, Suit 12, Plaza 212, Blanchardstown Business Park Phase 2, Blanchardstown, DUBLIN 15, Ireland [www.castrol.com/ie](http://www.castrol.com/ie)  
 Automotive Technical Helpline: 1800 509 353  
 Orders/Enquiries: 01 866 5100

---