

INSTALLATION INSTRUCTIONS

BMW S1000 RR | 2019 ---

EXHAUST SYSTEM: REMUS NXT Slip-on



SYMBOLS

The following symbols are used throughout these installation instructions:



TOOLS AND PROTECTIVE EQUIPMENT REQUIRED



TIGHTENING TORQUE



LUBRICATION



HAND TIGHTEN



INSTALLATION TIP



CAUTION OR IMPORTANT



MOVEMENT ARROW



INDICATOR ARROW



CERAMIC PASTE

For lubrication and corrosion protection on screws, bolts, fits and pins. Free of standard and heavy metals, prevents sticking and seizing, neutral to all known sealing materials, non toxic, up to +1400°C heat resistant, short term up to +1600°C, prevents wear and tear.



TOOLS AND EQUIPMENT

Use appropriate safety equipment like eye protection and mechanic gloves! Use appropriate and working tools for mounting and dismounting of the exhaust system.



We congratulate you on buying a product from REMUS and thank you for your trust. We are always striving to offer the very best product for your vehicle through continuous innovation processes and usage of the latest technologies.

READ THIS

Please read this entire installation manual carefully prior to installing and using the REMUS exhaust system.

REMUS exhaust system should only be installed by persons skilled in car exhaust system installation and performance. The instructions provided in this manual should be followed to ensure proper installation and safe use of the REMUS exhaust system. REMUS and/or its partners shall not be held liable for any damage or personal injury (including direct, indirect, or consequential damage) sustained as a result of improper installation of the REMUS exhaust system or its use and maintenance contrary to the instructions and warnings contained herein.

If you have any questions regarding the installation and/or proper use of the REMUS exhaust system or this manual, please contact your local REMUS partner.

For more information on the REMUS exhaust systems, see the official REMUS website at: http://www.remus.eu

GENERAL INFORMATION

Your safety is our number one priority. Please drive your car responsibly, safely and always obey local traffic rules.

All statements made with regard to the exhaust system's compliance are made in respect of the exhaust system "as is". Any modifications of the REMUS exhaust system or its improper installation, use or maintenance that is not in accordance with this Installation manual, may result in severe damage to the exhaust system and/ or engine, as well as personal injury, and may affect the exhaust system's compliance with the legal requirements, such as exhaust system's air and/ or noise emissions (as an example, the car may not be suitable for use on public roads any longer), as well as warranty coverage.

The exhaust system may only be used in accordance with relevant laws and regulations, including state and federal, where applicable.

Damage caused by improper installation, use and maintenance of the REMUS exhaust system is not covered by the REMUS warranty. Please refer to the enclosed warranty with regard to the terms of our warranty.

Technical specifications of REMUS exhaust systems and related products are subject to change without notice.



RIGHTS & NOTES

COPYRIGHT, OTHER RIGHTS NOTICE AND GENERAL NOTES

The REMUS trademark, including corporate logos and emblems, are subject to copyright as well as trademark rights of REMUS, its licensors, or third persons authorizing REMUS to use them. Any reproduction, technical or other manipulation, translation, or other use of the copyright and/or trademark rights contained herein is prohibited without the explicit prior written consent of REMUS.

The same especially applies to the entire contents of this manual and/or any of its parts, including but not limited to technical specifications, instructions, graphs, photographs, and so on included in this manual.

The photographs and other illustrations in this manual are symbolic and are intended to help represent individual steps for proper installation and use, as well as for a general overview.

The actual component parts of the REMUS exhaust system may not entirely correspond to the photographs and other illustrations.

REMUS takes all copyright and other rights infringement cases under serious consideration. If you have any reason to believe that your exhaust system is not an original REMUS product, please contact our local partners or REMUS at office@remus.at



SAFETY WARNINGS

IMPORTANT SAFETY WARNINGS, PLEASE READ CAREFULLY

The car should be in the off position throughout the whole dismounting and mounting process, as well as any other work done on the exhaust system!


Before dismounting the exhaust system, lock the car and remove the key from the car to avoid electronical errors in the car's control units!

For proper dismounting and mounting of the exhaust system, it is recommended to use an certificated and testet lifting device.

The exhaust system can get extremely hot during and after it is used. Allow the exhaust and engine to cool down before touching it and beginning installation.


Make sure that you have all the parts necessary for the installation of your new REMUS exhaust system, according to the parts list in this manual. If any of the parts are missing, please do not proceed with uninstalling your stock exhaust system/installing the REMUS exhaust system and contact the retailer you bought the REMUS exhaust system from.

CAUTION: make sure not to injure yourself or damage any part of the vehicle during dismounting and mounting of the exhaust systems!





pos	pcs	packing content
Α	1	sport exhaust
В	1	connection tube
С	2	hex socket screw M8x16 mm (premounted)
D	2	washer M8 (premounted)
Е	1	clamp
F	1	bracket
G	1	spring
Н	1	nut M8
I	1	washer M8
J	1	snap ring M8
К	1	copper paste
L	1	pair of gloves



REMOVAL

OF STOCK EXHAUST SYSTEM:

The process of uninstalling the original exhaust system may vary depending on the existing exhaust system. Please follow the original exhaust system manufacturer's instructions for uninstalling the original exhaust system.

If you for any reason decide otherwise, please note that any information provided in this respect herein should be considered as general information provided for your convenience only.

REMUS shall not assume any liability or responsibility with regard to uninstalling your existing exhaust system, warranty coverage of such exhaust system or vehicle or their further fitness for use.




REMOVAL OF STOCK EXHAUST SYSTEM:



Loosen the bracket's screw as well as the clamp and remove the serial mufflers.








INSTALLATION OF THE REMUS EXHAUST SYSTEM

Install the REMUS connection tube, by using the supplied clamp, onto the serial header.









Mount the supplied bracket on the REMUS sport exhaust. Slip the sport exhaust onto the connection tube, screw the bracket and hook the spring



Align the REMUS sport exhaust and tighten the connections.







TROUBLESHOOTING

EXHAUST VALVE ACTUATOR:

If the exhaust valve actuators are not moving:

- a) Check electrical connections and connectors
- b) Reset the actuators:
 - 1. Unplug the connectors on exhaust valve actuators
 - 2. Start the engine
 - 3. Stop the engine and wait for 1 minute
 - 4. Plug the connectors on exhaust valve actuators
 - 5. Start the engine
 - 6. Stop the engine and wait for 1 minute
 - 7. Start the engine (the actuators are reset)

FINAL INSTALLATION:

IMPORTANT: reinstall the dismounted or partially removed stock parts (wheel arches, bumper etc.); check vehicle manufacturer manual for tightening torques.

IMPORTANT: make sure all the nuts and bolts are sufficiently tightened. In case the exhaust system touches the cowling or other parts, repeat the adjustment of the exhaust system or contact your authorized dealer.

IMPORTANT: clean all exhaust components before the first start of the engine or the stains will burn onto the surfaces!



MAINTENANCE

MAINTENANCE OF THE REMUS EXHAUST SYSTEM:

- 1. Clean the titanium exhaust components with a multi-purpose spray lubricant (WD-40® or equivalent), carbon fiber exhaust components with soft and dry cloth and stainless steel components with soft cloth sprayed with contact cleaner, then wipe with soft and dry cloth. A change in the color of the exhaust system is normal due to high temperatures.
- 2. Periodically make sure all the bolts and springs are sufficiently tight.



IT IS NORMAL FOR WHITE SMOKE TO COME OUT OF THE MUFFLER AT FIRST OPERATION.

- (A) CAUTION: DO NOT STAND BEHIND THE MUFFLER AT ANY TIME.
- **(A)** CAUTION: DO NOT USE AUTOMOTIVE WHEEL CLEANERS OR ANY CLEANING

PRODUCTS WHICH CONTAIN ACIDIC ADDITIVES TO CLEAN THE REMUS EXHAUST SYSTEMS.

Problem	Possible cause	Solution
Exhaust gas leaks out of the	Loosened clamp	Tighten the clamp to specified torque
muffler/pipe clamp connections	Connection is not completely joined	Tap the connection into place and tighten the clamp to specified torque
Valvas are not moving	No supply	Check green LED on the Control Kit. If the LED is off: Check electrical connections and connectors Check fuse for exhaust valves (in the trunk, right)
Valves are not moving	Error detected	Check green LED on the Control Kit. If the LED is blinking fast: Check electrical connections and connectors Try to use the Sound Kit remote controller. If vlaves are turning, then check how thecommunication sensor is installed



THE SOUND OF CANS

FIRST CLASS QUALITY DESIGNED & BUILT IN EUROPE | AUSTRIA

www.remus.eu

REMUS Innovation GmbH
Ruhmannstraße 11
A-8570 Voitsberg